## ARI DC-500 / DC-501

### **SIZE**

1/2", 3/4", 1", 1 1/4", 1 1/2", 2"

### **DESCRIPTION**

This is a double check assembly. Production began in 2007. The body is made of a UV resistant glass reinforced nylon. There is a single access cover. The checks are an inline modular design. Spring tension is contained when the cover is removed. In 2016 the Model DC-501 was introduced with union end nylon shutoffs.

### **BASIC REPAIR KIT**

The kit contains discs and O'rings

<u>SIZE</u>	<u>KIT NO</u>		
1/2"-1"	0465-565499-01K		
1 1/4"-2"	0465-565499-02K		

### **IMPORTANT FEATURES**

- ~Plasic body construction
- ~Inline check design
- ~Factory repair information enclosed







# DC-500 Double Check Backflow Preventer

Sizes: 1/2" - 2"

### **HEAD LOSS**





### **Main Features**

- Working Pressure: 150 psi.
- Sizes: 1/2:"- 2"
- Temp: Up to 1100 f
- Made of composite plastic material, resistant to corrosion, to incrustation, to fertilizers, to herbicides, to insecticides, etc.
- Internal control system ensures reliability and safety.

### MATERIALS:

Body...... Polyamide 6.50% Glass Reinforced Nylon

Cover...... Polyamide 6.50% Glass Reinforced Nylon

Polymers... Noryl, NSF Listed

Elastomers... Silicone

Springs...... Stainless Steel

DC-500 Shut-off Valves - no-lead bronze

	Dim	Weigh		
	A	В	c	Lbs.
1/2"	11.81	4.39	3.94	3.62
3/4"	12,40	4.39	3.94	3.62
1"	12.99	4.39	3.94	4.49
11/4"	18.50	6.57	5.91	6.72
11/2"	19.02	6.57	5.91	7.83
2"	20.28	6.57	5.91	10.30

DC-501 Shut-off Valves - reinforced nylon

	Dimensions Inch			Weight
	A	В	c	Lbs.
3/4"	12.60	4.39	3.94	2.98
1"	14.17	4.39	3.94	2.92
11/4"	18.27	6.57	5.91	7.23
11/2"	20.47	6.57	5.91	8.71
2"	21.53.	6.57	5.91	8.85



